




Descrizione



Dimensioni costruttive



***237HM**
Per filettature M e G

Codice	Modello	Cilindrata	Flusso		Velocità	Press.	Dimensione								
		cm³/rev	at 1500 rpm	at max rpm	max rpm	bar	A	B	Aspirazione			Mandata			
			l/min				mm		E	d	F	E	d	F	
17030C(A)020X237H0	P30-20D(S)-237H	20	28,2	56,4	3000	250	56,1	116,7	40	M8	19	40	M8	19	
17030C(A)225X237H0	P30-22,2D(S)-237H	22,5	31,7	63,5	3000	250	57,6	119,7							
17030C(A)025X237H0	P30-25D(S)-237H	25	35,3	70,5	3000	250	58,3	121,1							
17030C(A)028X237H0	P30-28D(S)-237H	28	39,5	79	3000	250	60,2	124,7							
17030C(A)032X23700	P30-32D(S)-237	32	45,1	75,2	2500	250	62,0	128,3	51	M10	27				
17030C(A)032X237H0	P30-32D(S)-237H	32	45,1	90,2	3000	250	66,5	137,3							
17030C(A)036X23700	P30-36D(S)-237	36	50,8	84,6	2500	250	63,5	131,4							
17030C(A)036X237H0	P30-36D(S)-237H	36	51,3	95,8	2800	250	68	140,5							
17030C(A)042X23700	P30-42D(S)-237	42	59,9	91,8	2300	230	66,3	137,0							
17030C(A)042X237H0	P30-42D(S)-237H	42	59,9	99,8	2500	230	70,8	146,1							
17030C(A)046X237H0	P30-46D(S)-237H	46	65,6	100,5	2300	230	72,7	149,8							
17030C(A)050X237H0	P30-50D(S)-237H	50	71,3	99,8	2100	200	74,5	153,4							
17030C(A)055X237H0	P30-55D(S)-237H	55	78,4	91,4	1750	200	76,7	157,9							
17030C(A)060X237H0	P30-60D(S)-237H	60	85,5	99,8	1750	180	78,7	162,4							